



USEFUL TIPS

- Be mindful of the cord or wire crossing or twisting during setup. (see instructional video)
- When using wire, be conscious of possible spring-back when wire gets unspooled.
- When using your drill of choice, we recommend a low speed setting for a smooth cut. Using a higher speed may cause the cord to break or wire to snap.

DO NOT USE IMPACT TOOLS WITH YOUR TRANSFORMER®

TFM50 Includes:

- Transformer® Quarter Glass Removal Tool PRM338 -Ratchet
- TSD192 - Drill Bit
- SDS192 - SideStriker™
- I-SDS-FP - Protection Pad
- GSS220 - Guide Sheets
- RC100 - RipCordHD™
- SFR350 - SwiftCutPro® 350

Scan for Instructional Video



INSTRUCTIONS

QUARTER GLASS REMOVAL WITH SIDESTRIKER™

- Remove all trim panels surrounding the work area and identify any clips/setting pins. Make sure to use proper vehicle and personal protection.
- Insert cord on the spindle on one side of the Transformer®, lace cord around perimeter of the quarter glass on the outside. Anchor using Equalizer® Large or Mini anchor cup (sold separately) to the vehicle.
- Attach the SideStriker™ to the door striker, insert Transformer® to the SideStriker™ and secure with locking pin.
- Apply tape on the glass and body as well so that when the last cut is made, the glass will stay in place.
- Using either the ratchet (included) or your drill with provided drill bit, begin cutting until your cut-out is complete.
- When you encounter the clips, make sure that the wire/cord stays between the clip and the body of the vehicle.
- As you begin cutting again, keep in mind that the glass is now loose, so slow and easy movements are required. If not, you could pop the glass out too soon causing damage to the glass and or body of the vehicle. Continue cutting until wire/cord crosses making the final cut.





WARRANTY TERM

Equalizer® Transformer® is warrantied for ONE year to be free of factory defects from the date of purchase.

WHAT IS COVERED?

Equalizer® warrants this product is free from defects in materials and workmanship when used for the purpose intended, under normal conditions, and provided it receives the proper care and maintenance as described in the User Guide section. This warranty is good only for authentic, original, legitimate tools manufactured by Equalizer® and sold through Authorized Distributors or from Equalizer® directly. These terms cover the following items for one year from purchase date: locking pins, spindles, anchor mechanism.



WHAT IS NOT COVERED?

- Warranty does not apply to abuse, misuse, normal wear and tear, or to accessories.
- Damage caused where repairs have been made or attempted by unauthorized persons.
- Using wire and/or cord other than the Authorized and recommended Equalizer® wire and/or cord will automatically void warranty.
- Using IMPACT Tools will automatically void warranty.

WARRANTY INFORMATION

WARRANTY CLAIMS

Equalizer® will repair or replace, at our discretion, any defective part. Our goal is for tools to be repaired and sent back the same day they are received.

Equalizer® reserves the right to refuse repair, at our expense, any tool which has not been properly maintained as specified in the User Guide and Warranty Section.

To send in your tool for repair, contact Equalizer® to receive a RMA number. If you have any questions about your tool call us at 512.388.7715, or email sales@equalizer.com.

Please send the entire tool to:
Equalizer®
Attention: Repair Department/ RMA# _____
2611 Oakmont Drive Round Rock, TX 78665 USA

Scan to Request an RMA
for Tool Repair

